

Specifications

FOX3 Matrix 320x

TRUE 4K specification

Max. 4K Capabilities		
Resolution and Refresh Rate	Chroma Sampling	Max. Bit Depth per Color
4096 x 2160 at 60 Hz ¹	4:4:4	8 bit
3840 x 2160 at 60 Hz ¹		10 bit
4096 x 2160 at 30 Hz ¹	4:2:2	12 bit
3840 x 2160 at 30 Hz ¹		
4096 x 2160 at 60 Hz ²	4:4:4	
3840 x 2160 at 60 Hz ²		
4096 x 2160 at 30 Hz ²		
3840 x 2160 at 30 Hz ²		

Frame rate³ 24, 25, 30, 50, or 60 fps

Chroma sampling³ 4:4:4, 4:2:2

Color bit depth^{2,3} 8, 10, or 12 bits per color

Signal type HDMI 2.0, HDCP 2.3

Max. video data rate 18.0 Gbps

NOTE: ¹Supports lossless 4K video over one fiber or uncompressed 4K video over two fibers.

²Supports 12-bit color bit depth for uncompressed 4K video over two fibers. When using a FOX3 SR scaling receiver, the scaler must be in bypass mode to pass 4K video with a 12-bit color bit depth.

³Subject to the maximum data rate limit. Use our calculator at www.extron.com/8Kdatarate to determine video parameters supported by this data rate.

NOTE: This product contains Class 1 laser. It meets the safety regulation of IEC 60825-1, FDA 21 CFR 1040.10, and FDA 21 CFR 1040.11.

Optical specifications

Number/type 8 singlemode or 8 multimode SFPs per board

Connectors 16 LC connectors per I/O board

Signal type 8 to 320 fiber optic signals

Routing 8 x 8 up to 320 x 320 unidirectional matrix or
4 x 4 up to 160 x 160 bidirectional matrix

Operating distance

Singlemode 20 km (12.4 miles) with singlemode (SM) cables

Multimode 500 m (1640 feet) with 50 µm OM4 4700 MHz bandwidth laser optimized multimode cables

NOTE: The system works with OM1, OM2, and OM3 fiber at reduced distances.

Specifications • FOX3 Matrix 320x (Continued)

NOTE: Operating distance is approximate. These are typical distances. The maximum distance may be greater than these typical numbers depending on factors such as fiber type, fiber bandwidth, connector splicing, losses, modal or chromatic dispersion, environmental factors, and kinks.

Nominal peak wavelength 850 nm for multimode (MM), 1310 nm for singlemode (SM)

Transmission power

Singlemode -5.2 dBm, typical

Multimode -3.3 dBm, typical

Maximum receiver sensitivity

Singlemode -12.6 dBm, typical

Multimode -13.0 dBm, typical

Optical loss budget

Singlemode +7.4 dB, maximum

Multimode +9.7 dB, maximum

Maximum channel data rate 10 Gbps

Audio input/output board

Number/signal type 4 analog stereo inputs, balanced/unbalanced

4 analog stereo outputs, balanced/unbalanced

Connectors (8) 3.5 mm captive screw connector, 5 pole

Source formats 2 channel LPCM

Impedance ≥10 k ohms unbalanced, ≥20 k ohms balanced

Nominal level +4 dBu (1.23 Vrms), -10 dBV (316 mVrms)

Maximum level +21 dBu balanced, +15 dBu unbalanced

Gain range Adjustable, -18 dB to +24 dB, 1 dB steps

Gain Unbalanced output: -6 dB; balanced output 0 dB (default)

Frequency response 20 Hz to 20 kHz, ±0.5 dB

THD + Noise <0.1% @ 20 Hz to 20 kHz at nominal level

S/N >90 dB at maximum output (unweighted)

CMRR 65 dB @ 20 Hz to 20 kHz

Output impedance 50 ohms unbalanced, 100 ohms balanced (analog only)

Maximum level (Hi-Z) +21 dBu balanced, +15 dBu unbalanced

Gain error ± 0.5 dB channel to channel

Volume control range -100 dB to 0 dB (0-100 in 1 dB steps)

Crosstalk ≤-80 dB @ 1 kHz, fully loaded

Stereo channel separation >80 dB @ 1 kHz

Bit depth 16, 20, 24

Sampling rate 48 kHz

NOTE: 0 dBu = 0.775 Vrms, 0 dBV = 1 Vrms, 0 dBV ≈ 2 dBu

AT ports — Dante audio transport

Transmission type Dante/AES-67, software selectable

Connectors 2 RJ-45 to Dante interface

Inputs Up to 32 stereo channels

Outputs Up to 32 stereo channels

Audio format 24 bit uncompressed at 48 kHz sampling rate

Latency Deterministic, based on user selections: 0.25 ms, 0.5 ms, 1.0 ms (default), 2.0 ms, 5.0 ms

EXP port

Transmission type Proprietary

Connector 1 RJ-45

Inputs 8 stereo channels Rx

Specifications • FOX3 Matrix 320x (Continued)

Outputs	8 stereo channels Tx
Audio format	Uncompressed, 24-bit, 48 kHz
EXP cable	Shielded CAT6 up to 10 meters

Communications

USB configuration port	
Number/type	1 front panel mini USB B, female
Standard	Ethernet over USB
Serial control port.....	1 RS-232, 3.5 mm captive screw connector, 3-pole, female, rear panel
Baud rate and protocol.....	300 to 115200 baud (default: 9600), 8 data bits, 1 stop bit, no parity
Serial control pin configuration	Captive screw: 1 = Tx, 2 = Rx, 3 = GND
Ethernet control	
Ethernet port	1 RJ-45 connector, female
Ethernet data rate.....	10/100/1000Base-T, half/full duplex with autodetect
Protocols.....	ARP, ICMP (ping), DHCP, DNS, HTTPS, SFTP, SSH, TCP/IP, UDP/IP
Default settings.....	Link speed and duplex level = autodetected IP address = 192.168.254.254 Subnet mask = 255.255.255.0 Gateway = 0.0.0.0 DHCP = off
Web server	Up to 200 simultaneous sessions 7.0 MB non-volatile memory
Program control.....	Extron Product Configuration Software Extron Simple Instruction Set (SIS™)

General

Power supply	Internal, 2* (positive-negative), primary and redundant, hot-swappable Input: 100-240 VAC, 50-60 Hz
	*A redundant power supply is standard.
Power consumption.....	Enclosure without boards: 178 watts Enclosure fully loaded with 40 MM boards: 1001 watts Enclosure fully loaded with 40 SM boards: 1165 watts Each MM board: 20.1 watts Each SM board: 23.1 watts
Temperature/humidity	Storage: -40 to +158 °F (-40 to +70 °C) / 10% to 90%, noncondensing Operating: +32 to +122 °F (0 to +50 °C) / 10% to 90%, noncondensing
Cooling	Fan, right to left (as viewed from front panel)
Thermal dissipation, full load	MM: 3416 BTU/hr SM: 3977 BTU/hr
Mounting	
Rack mount.....	Yes
Enclosure type	Metal
Enclosure dimensions	21.0" H x 17.0" W x 20.0" D (12U high, full rack wide) (53.3 cm H x 43.2 cm W x 50.8 cm D) (Depth excludes connectors and handles. Width excludes rack ears.)
Product weight (fully loaded)	126 lbs (57 kg)
Regulatory compliance.....	CE, c-UL, C-tick, FCC Class A, ICES, UL, VCCI Complies with the appropriate requirements of RoHS, WEEE.
Product warranty	3 years parts and labor

NOTE: All nominal levels are at ±10%.

NOTE: Specifications are subject to change without notice.

NOTE: Shipping weights and dimensions are available at www.extron.com.