

# **Specifications HSA 400, HSA 402 Series**

#### **General**


**NOTE:** The Universal AC outlet is fully compatible with Europlug, British, Indian, Danish, and Italian plug types. See the Universal AC outlet guide on the Extron website, **www.extron.com**, for compatibility details on all plug types.

#### Mounting

Furniture mount ...... Yes

Min./max. table thickness .............. 0.38" to 1.75" (9.5 mm to 45 mm)

Enclosure type ...... Metal



#### Enclosure dimensions

**CAUTION:** Use the appropriate metal Extron routing template or refer to the surface cutout dimensions here before cutting a hole in the furniture or other surface. Pay special attention to the direction the unit will face; the unit's AAP and connector access side is underlined. Extron is not responsible for miscut mounting holes.

### HSA 400 (US)

Clamshell (see diagram) .....  $\mathbf{A} = 5.25$ " (133 mm)

**B** = 7.75" (197 mm) **C** = 7.75" (197 mm)

HSA 402 (US)

Clamshell (see diagram) .....  $\mathbf{A} = 5.19$ " (132 mm)

**B** = 9.80" (249 mm) **C** = 7.75" (197 mm)

## Specification • HSA 400, HSA 402 Series (Continued)

Clamshell (see diagram) ..... **A** = 5.17" (131 mm)

**B** = 9.17" (233 mm) **C** = 7.77" (197 mm)

HSA 402 (International)

Clamshell (see diagram) .....  $\mathbf{A} = 5.19$ " (132 mm)

**B** = 12.8" (325 mm) **C** = 7.77" (197 mm)

**NOTE:** Specifications are subject to change without notice.

**NOTE:** Shipping weights and dimensions are available at **www.extron.com**.

4211-D14-020818