TLP Pro 1025T

10" TABLETOP TOUCHLINK PRO TOUCHPANEL



The Extron TLP Pro 1025T is a 10" tabletop TouchLink® Pro Touchpanel with many enhanced features. Extron redesigned this latest TouchLink Pro Touchpanel inside and out with a new, high-performance quadcore processor, eight times more memory, a higher resolution, 1280x800 capacitive touchscreen built with scratch and smudge-resistant Corning® Gorilla Glass®, and a distinctive enclosure with a sleek, gracefully-sweeping back. The TLP Pro 1025T also features the convenience of PoE - Power over Ethernet, which allows it to receive power and communication over a single Ethernet cable.

- ▶ 10" capacitive edge-to-edge glass touchscreen with 1280x800 resolution and 24-bit color depth
- Newly designed inside and out for the ideal balance of performance and style
- Gorilla Glass® screen is tough, scratch and smudge-resistant
- Faster, quad-core processing and eight times more memory
- ▶ Compatible with all IP Link Pro control processors
- Power over Ethernet provides power and communication over a single Ethernet cable
- Light sensor adjusts screen brightness as the ambient room lighting changes




DESCRIPTION


The **TLP Pro 1025T** is a 10" tabletop touchscreen that offers stellar performance and superior design. Inside, there's a powerful new quad-core processor and eight times more memory feeding the high resolution 1280×800 capacitive touchscreen. The touchscreen, itself, is our most durable yet - built with scratch and smudge-resistant Corning Gorilla Glass. Outside you'll find a stylish, ergonomic enclosure that will complement any contemporary presentation environment.


A host of familiar features provides elegant, simple operation, while PoE, Power over Ethernet streamlines integration by allowing the touchpanel to receive power and communication over a single Ethernet cable.


All TouchLink Pro touchpanels can be customized using Extron GUI Designer software. This powerful interface design software offers ready-to-use templates for a wide variety of rooms and presentation environments.

PANEL DRAWINGS









SPECIFICATIONS

DIODI AV	
DISPLAY	TTT A 11
Screen type	TFT Active matrix Color LCD
Size	10.1" (25.7 cm), measured diagonally
Resolution Aspect ratio	1280x800 Widescreen
Aspect ratio Color depth	
Contrast	24 bit, 16.7 million colors
	800:1 LED
Backlight Viewing angle	±85° horizontal, ±85° vertical
Touch screen	Capacitive
	Capacitive
MEMORY	
SDRAM	2 GB
Flash	4 GB
COMMUNICATION - ETHERN	IET INTERFACE
Ethernet control/communications port	1 female RJ-45 connector
Ethernet data rate	10/100/1000Base-T, half/full duplex with autodetect
Ethernet protocol	DHCP, DNS, HTTP, HTTPS, ICMP, SFTP, SSH, TCP/IP, UDP/IP
CONTROL – USB	
	1 high around LICD 2.0 daying
Number/signal type	1 high-speed USB 2.0 device
AUDIO OUTPUT	
Speaker output	1 mono, 86 dB SPL, 0.1 watt, 0.1 m, half space
Playback format(s)	
Container format	WAV (Microsoft RIFF)
Encoding	LPCM (uncompressed)
Bit depth	Unsigned 8-bit
	Signed 16-bit
	Signed 24-bit
	Signed 32-bit
Sampling rate	Up to 192 kHz
Audio channels	mono or stereo
GENERAL	
Power supply	Not included
Power input requirements	Power over Ethernet (PoE 802.3af, class 3)
Auxiliary power output	
USB	5 VDC, 275 mA
Temperature/humidity	Storage: -4 to +158 °F (-20 to +70 °C) /
	5% to 90%, noncondensing
	Operating: -4 to +158 °F (-20 to +70 °C) /
	20% to 90%, noncondensing
Mounting	Set on a tabletop
Englacura dimanaiana	C 0.4" II.v 10.10" W.v. 4.15" D
Enclosure dimensions	6.84" H x 10.10" W x 4.15" D
Regulatory compliance	(174 mm H x 257 mm W x 105 mm D)
Safety	CE, c-UL, UL
EMI/EMC	CE, C-TICK,FCC Class A, ICES, KCC, VCCI
Environmental	Complies with the appropriate requirements of RoHS and
Environmontal	WEEE.
Warranty	3 years parts and labor; touchpanel display and overlay
'	components are covered for 1 year
Model Version Descriptio	
TLP Pro 1025T Black - Tabletop	60-1565-02
TLP Pro 1025T White - Tabletop	60-1565-03
	ications please an to wave extron com

For complete specifications, please go to www.extron.com Specifications are subject to change without notice.

- WORLDWIDE SALES OFFICES

Anaheim • Raleigh • Silicon Valley • Dallas • New York • Washington, DC • Toronto • Mexico City • Paris • London Frankfurt • Madrid • Stockholm • Amersfoort • Moscow • Dubai • Johannesburg • Tel Aviv • Sydney • Melbourne Bangalore • Mumbai • New Delhi • Singapore • Seoul • Shanghai • Beijing • Hong Kong • Tokyo