

# DATA SHEET

## VOCIA® WS-10

### WALL PAGING STATION



The WS-10 is a wall-mounted networked paging station for use in Vocola® systems. The WS-10 features embedded DSP and on-board memory to support standard and advanced public address functionalities. The WS-10 can store 999 user-configurable page codes. Additionally, all device-specific configuration information is stored locally, which means the WS-10 does not rely on a centralized controller for processing and page routing. Thus, the processing, routing and storage functionality in a Vocola system is decentralized, which eliminates any centralized point of failure. As part of the Vocola system, the WS-10 meets paging requirements for facilities of all sizes.

#### FEATURES

- Push-to-talk button with status indication
- Up to 999 user-configurable page codes
- Four software configurable non-emergency priority paging levels
- Local digital signal processing, including gain, filters, and compressor/limiter
- Local storage of configuration data
- Local storage of default and/or custom preambles
- Built-in store and forward functionality
- CobraNet® audio/control with dynamic use of available bundles, plus power over single Ethernet cable
- Backlit liquid crystal display (LCD) technology
- Optional PIN to restrict unauthorized use
- Auxiliary Port provides connection for power, line-level audio, and bi-directional RS232 for transmitting Vocola Text Protocol (VTP) commands
- High-quality, noise-cancelling handheld microphone
- Sturdy, surface-mounted component housing
- Rotary ID switches for unit identification
- CE marked and RoHS compliant
- Covered by Biamp Systems' 5-year warranty

## ARCHITECTS & ENGINEERS SPECIFICATION

The wall-mounted paging station shall be designed exclusively for use with Biamp® Vocola® systems. The wall-mounted paging station shall provide paging audio and control data via CobraNet®, and receive Power over Ethernet (PoE), utilizing a single (CAT5) network cable to a rear panel RJ-45 connector. Ten buttons shall be provided on the front panel for recalling page codes with preambles. Multiple wall-mounted paging stations may be connected to a Vocola system by means of Ethernet switches. Four software configurable non-emergency priority paging levels shall be available. The wall mounted paging station shall include page priority override, store and forward, and lock-out capabilities. Each wall-mounted paging station shall provide local digital audio signal processing, local storage of configuration data, and preambles. Wall-mounted paging stations shall possess a backlit LCD screen, PIN code accessibility, and a high-quality, noise-cancelling handheld microphone. The wall-mounted paging station shall be CE marked and shall be compliant with the RoHS directive. Warranty shall be five years. The wall-mounted paging station shall be a Vocola WS-10.

## VOCIA WS-10 SPECIFICATIONS

<b>Network Connection:</b>	RJ-45 with shielded Ethernet (CAT5, CAT5e, CAT6 or CAT7)	<b>Power:</b>	
<b>Frequency Response (100Hz ~ 20kHz):</b>	+0, -1dB	<b>PoE:</b>	802.3af Class 2
<b>THD+N (100Hz ~ 8kHz):</b>	<0.05%	<b>Aux:</b>	24V DC 6W
<b>Effective Input Headroom:</b>	30dB	<b>Overall Dimensions (excl. microphone):</b>	
<b>System Headroom:</b>	18dB	<b>Height:</b>	5.3 inches (135 mm)
<b>Gain:</b>	Adjustable in 1dB steps over a 30dB range	<b>Width:</b>	11.9 inches (302 mm)
<b>Maximum Input:</b>	125dB SPL	<b>Depth:</b>	1.9 inches (48 mm)
<b>Mic Type:</b>	Noise cancelling dynamic microphone with dual transducer (monitored)	<b>Weight:</b>	2.6 lbs (1.2 kg)
<b>Mic Pattern:</b>	Cardioid	<b>Mic Cord Length (extended):</b>	4 ft. (1219 mm)
<b>Mic Frequency Response:</b>	100Hz-10kHz	<b>Environment:</b>	
<b>Auxiliary Port:</b>		<b>Ambient Operating Temperature Range:</b>	23-104° F (-5 - 40° C)
<b>PTT:</b>	Switch contact between pin and ground	<b>Humidity:</b>	0 - 95% non-condensing
<b>12V DC Out:</b>	50mA	<b>Altitude:</b>	0-10,000 Feet (0-3000 Meters) MSL
<b>RS-232:</b>	57600 kbps	<b>Sample Rate:</b>	48kHz
<b>Balanced Line In:</b>	-10dB Nominal	<b>A/D Converters:</b>	24-bit
<b>Input Impedance:</b>	3kΩ	<b>Compliance:</b>	
			CE marked (Europe) UL and C-UL listed (USA and Canada) RoHS Directive (Europe)

## VOCIA WS-10 WALL-MOUNTING BRACKETS

