

Specifications

XTP II CrossPoint® 1600 Enclosure

TRUE 4K specification

Max. 4K Capabilities		
Resolution and Refresh Rate	Chroma Sampling	Max. Bit Depth per Color
4096x2160 at 60 Hz	4:4:4	16 bit
3840x2160 at 60 Hz		

Frame rate 24, 25, 30, 50, or 60 fps
Chroma sampling..... 4:4:4, 4:2:2, or 4:2:0
Color bit depth..... 8, 10, 12, or 16 bits per color
Backplane throughput..... 50 Gbps per input and output

NOTE: Use our calculator at www.extron.com/4Kdatarate to determine video parameters supported by this data rate.

AV routing capabilities

Number of input slots..... 4
Input video signal format..... HDMI, DVI, 3G-SDI, RGBHV, RGBS, RGsB, RsGsBs, YUV, S-video, composite video, XTP twisted pair, XTP fiber
Input audio signal format PCM up to 8 ch, Dolby Atmos®, Dolby® TrueHD, Dolby Digital Plus™, Dolby Digital EX, Dolby Digital, DTS-HD Master Audio™, DTS-HD High Res, DTS 96/24, DTS-ES®, DTS, analog stereo
Number of output slots 4
Output video signal format..... HDMI, DVI, XTP twisted pair, XTP fiber
Output audio signal format PCM up to 8 ch, Dolby Atmos, Dolby TrueHD, Dolby Digital Plus, Dolby Digital EX, Dolby Digital, DTS-HD Master Audio, DTS-HD High Res, DTS 96/24, DTS-ES, DTS, analog stereo
Backplane
Switcher..... 16x16 matrix
Maximum throughput 50 Gbps

Communications – switcher host ports

NOTE: The front panel USB port and rear panel RS-232 port are independent of each other and can be used at the same time.

Serial host control port..... 1 bidirectional RS-232 or RS-422, rear panel female 9-pin D connector
Baud rate and protocol 9600 (default) to 115200 baud, 8 data bits, 1 stop bit, no parity, no flow control
Serial control pin configurations
RS-232 2 = Tx, 3 = Rx, 5 = GND
RS-422 2 = Tx-, 3 = Rx-, 5 = GND, 7 = Rx+, 8 = Tx+
USB control port..... 1 front panel female mini USB B
USB standards USB 2.0, low speed

Ethernet control port	1 female RJ-45
Ethernet data rate (for network communication)	10/100Base-T, half/full duplex with autodetect
Ethernet protocol	ARP, ICMP (ping), IP, TCP, DHCP, HTTP, SMTP, Telnet
Ethernet default settings	Link speed and duplex level = autodetected IP address = 192.168.254.254 Subnet mask = 255.255.0.0 Default gateway = 0.0.0.0 DHCP = off
Web server	Up to 200 simultaneous sessions 7.0 MB nonvolatile user memory
Program control	Extron XTP System Configuration Software for Windows® Extron Simple Instruction Set (SIS™) Microsoft® Internet Explorer® ver. 6 or higher, Telnet

General

Power	Internal Input: 100-240 VAC, 50-60 Hz Redundant power supply is standard.
Power consumption	45 to 637 watts, depending on the configuration
With primary power supply only	
115 VAC, 60 Hz	47.0 watts
240 VAC, 50 Hz	45.0 watts
With both primary and redundant power supplies	
115 VAC, 60 Hz	50.3 watts
240 VAC, 50 Hz	48.9 watts
Remote power capability	Supports up to 28 XTP twisted pair endpoints
Temperature/humidity	Storage: -40 to +158 °F (-40 to +70 °C) / 10% to 90%, noncondensing Operating: +32 to +122 °F (0 to +50 °C) / 10% to 90%, noncondensing
Cooling	Fan, right to left (as viewed from front panel)
Thermal dissipation	154 to 2108 BTU/hr, depending on the configuration
Mounting	
Rack mount	Yes
Enclosure type	Metal
Enclosure dimensions	8.75" H x 17.0" W x 17.5" D (5U high, full rack wide) (22.2 cm H x 43.2 cm W x 44.5 cm D) (Depth excludes connectors. Width excludes rack ears.)
Product weight with boards installed	
	39.0 lbs (17.7 kg)
Vibration	ISTA 1A in carton (International Safe Transit Association)
Regulatory compliance	
Safety	CE, c-UL, UL
EMI/EMC	CE, C-tick, FCC Class A, ICES, VCCI, KCC
Environmental	Complies with the appropriate requirements of RoHS, WEEE.
Warranty	3 years parts and labor

NOTE: All nominal levels are at ±10%.

NOTE: Specifications are subject to change without notice.

NOTE: Shipping weights and dimensions are available at www.extron.com.